SYSTEM AND METHOD FOR CONTROLLING A TEMPERATURE OF AN EMISSION CONTROL DEVICE

Field Of The Invention

The present invention relates to a system

5   and method for controlling a temperature of an
emission control device.

Description Of The Related Art

Diesel engines have utilized emission
control devices such as NOx absorbers or NOx traps to

10   remove NOx from engine exhaust gases. Engine control
systems generally create exothermic reactions in the
emission control devices to heat the devices for
improved NOx reduction. However, engine control
systems have difficulty in controlling a temperature

15   in the emission control devices which can result in
an excess temperature that degrades the devices.
Thus, the inventors herein have recognized there is a
need for a system and method for accurately
controlling the temperature of the emission control

20   device.

Summary of the Invention

The foregoing problems and disadvantages

25   are overcome by a system and method for controlling a
temperature in an emission control device.
A method for controlling a temperature of
an emission control device receiving exhaust gases
from an engine is provided. The emission control

30   device is coupled adjacent and downstream of an
oxidation catalyst. The method includes adding a
reductant to the exhaust gases. The method further

includes controlling a mixture of the exhaust gases and the reductant flowing into the oxidation catalyst to control a temperature of the emission control device.

5   A system for controlling a temperature of an emission control device receiving exhaust gases from an engine is also provided. The device is coupled adjacent and downstream of an oxidation catalyst. The system includes a reductant valve

10   selectively supplying reductant to the exhaust gases responsive to a first signal. The system further includes a throttle valve controlling flow of the exhaust gases to the oxidation catalyst responsive to a second signal. The system further includes a

15   controller operably connected to the reductant valve and the throttle valve. The controller generates the first and second signals to control a mixture of the exhaust gases and the reductant flowing into the oxidation catalyst to control a temperature of the

20   emission control device.

          The system and method claimed herein provide a substantial advantage over known systems and methods. In particular, by controlling a temperature of an oxidation catalyst adjacent the

25   emission control device, the temperature of the device can also be accurately controlled. In particular, by controlling a mixture of exhaust gases and reductant flowing into the oxidation catalyst, the temperature of the mixture exiting the catalyst

30   can be maintained within a desired temperature range, preventing degradation of the device.

Brief Description Of The Drawings

Figure 1 is a plan view of an exhaust
5   system coupled to an engine.

Figure 2 is a schematic diagram of a dual
NOx trap and particulate filter of the exhaust system
of Figure 1.

Figures 3A, 3B are flowcharts of a method
10   for monitoring and removing stored NOx from the
exhaust system of Figure 1.

Figures 4A, 4B, 4C are flowcharts for
monitoring and removing particulate matter and sulfur
oxides (SO_x) stored in the exhaust filters of Figure
15   1.

Figures 5A and 5B are schematics of signals
illustrating the operation of the flowchart of Figure
4B for removing particulate matter from an exhaust
filter.

20   Figures 6A and 6B are schematics of signals
illustrating the operation of the flowchart of Figure
4C for removing particulate matter and SO_x from an
exhaust filter.

25   **Description of the Preferred Embodiments**

Referring now to Figure 1, an exhaust
system 10 is illustrated in operational relationship
with an internal combustion engine 12 such as a
diesel engine for a vehicle such as an automotive
30   vehicle (not shown). The engine 12 has an exhaust
manifold 14 to direct the exhaust gases from engine
12 to exhaust system 10. The exhaust manifold 14 is
divided into two exhaust intake conduits 16, 18. The

3

exhaust intake conduits 16, 18 direct exhaust gases through two integrated NO_x trap/particulate filters 19, 20. The outputs of the filters 19, 20 are directed through two exhaust output conduits 21, 22

5   to a muffler or tail pipe 23. The amount of exhaust gases flowing to filters 19, 20 is controlled by control valves 24, 25, respectively. Conventional oxidation catalysts 26, 27 are located upstream and proximate filters 19, 20, respectively.

10   The oxidation catalysts 26, 27 serve several functions. First, catalysts 26, 27 are utilized to accurately control temperatures in filters 19, 20, respectively. Fuel injected into the exhaust gases upstream of catalysts 26, 27 can be

15   used to create exothermic reactions in catalysts 26, 27 to provide exhaust gases at desired temperatures to filters 19, 20, respectively. Thus, temperature spikes produced by the injected fuel only occur within catalysts 26, 27 instead of filters 19, 20---

20   thereby protecting filters 19, 20 from degrading due to excess temperatures. Further, controlled exothermic reactions in catalysts 26, 27 allow filters 19, 20 to be maintained within desired temperature ranges and air-fuel ranges for optimally

25   removing NOx, SO_x, and particulate matter. It should be understood, however, that an oxidation catalyst as taught by this specification can be used to control a temperature of any proximate downstream emission control device such as a NOx absorber, a catalytic

30   converter, and a particulate filter, for example. Second, catalysts 26, 27 begin burning the fuel injected into the exhaust gases and rapidly vaporize the remaining fuel before the mixture of fuel and

exhaust gases reach filters 19, 20, respectively.
The vaporized fuel more effectively reduces NOx
within filters 19, 20 as compared to injecting liquid
fuel directly into filters 19, 20.

5   A reducing agent supply tank 28 and
associated fuel nozzles 29, 30 enable precise
quantities of reductant, such as diesel fuel, to be
injected into the exhaust path intake conduits 16,
18.   In the case of a diesel engine, the reductant is

10   preferably the diesel fuel supply in the vehicle fuel
tank.   It should be understood, however, that other
reductants such as gasoline for example could be used
as the injected reductant.

          In addition, temperature sensors 31, 32

15   generate feedback signals to the engine control
module (ECM) 34.   The signals are indicative of
temperatures of exhaust gases exiting catalysts 26,
27, respectively---obtained from exothermic reactions
in oxidation catalysts 26, 27.   The ECM 34, in turn,

20   controls the flow of exhaust gases through exhaust
system 10 as well as the regeneration process of
filters 19, 20.   Logic control of system 10 is
carried out in ECM 34 by way of a central processing
unit (CPU) 36 such as a microprocessor 36 and an

25   associated memory 38.

          Referring to Figures 1 and 2, each of the
exhaust filters 19, 20 may include a filter substrate
40 extending along a longitudinal axis.   The filter
substrate 40 has a plurality of walls 42 extending

30   longitudinally and forming a plurality of alternating
first and second channels 44 and 46.   The walls 42
may be made of a ceramic material such as ceramic
cordierire.   The ceramic material is porous and has a

pore size of approximately 60 microns. The walls 42
have a thickness of 10 to 20 mils. The walls 42 are
configured to provide 50 to 200 channels per square
inch. Channels 44, 46 have a generally rectangular

5   cross-section, although it should be appreciated that
the cross-sectional area of the channels 44,46 is
dictated by flow and filtering requirements.

Each of channels 44, 46 have an inlet end
48 and an outlet end 50. The first channels 44 have

10 a blocking member 52 to close the outlet end 50 and
the second channels 46 have a blocking member 52 to
close inlet end 48. The blocking member 52 is made
of ceramic material such as ceramic cordierite.
Second channels 46 also have a NO_x absorbent wash coat

15 54 extending from the outlet end 50 along the walls
42 toward the inlet end 48. The wash coat 54 is a NO_x
absorbent applied by conventional procedures. The NO_x
absorbent may be (i) a precious metal such as Pt-Rh
and an alkali metal such as potassium or lithium, or

20 (ii) alkaline earth metals such as barium or
strontium or (iii) lanthanides such as cerium---
dispersed into an alumina support deposited onto
walls 42 of second channels 46.

It should be appreciated that alternate

25 channels 44, 46 are blocked to force all of the
exhaust gas flow through walls 42 having wash coat 54
thereby filtering the exhaust gas particulate matter
and absorbing the NO_x. Exhaust gases from engine 12
enter through the inlet openings 48, pass through

30 porous walls 42 of the substrate 40, and exit through
the second channels 46 at open outlets 50. Since the
particulate matter is too large to pass through the
pores within substrate wall 42, it deposits onto

surface 55 of the open channels 44. The NO_x, HC, and CO pass readily through the substrate wall 42. NO_x is stored as a nitrate complex while HC and CO are oxidized over the platinum within NO_x trap wash coat

5   54.

Referring to Figures 1 and 2, under the control of ECM 34, all of the exhaust gases flowing from engine 12 may be directed, for example, to first exhaust intake conduit 16 and corresponding catalyst

10   26 and filter 19 by controlling valves 24, 25. In this example, control valve 24 is completely open and control valve 25 is completely closed. In this manner, all of the exhaust gases from engine 12 will flow through exhaust intake conduit 16, through

15   oxidation catalyst 26, filter 19, exhaust output conduit 21, and exit tail pipe 23. When a mixture of exhaust gases and fuel are rich of stoichiometry, the majority of the CO and HC in the exhaust gases are oxidized in oxidation catalyst 26, and the remaining

20   CO and HC is oxidized over the platinum contained within the NO_x trap-particulate filter 19.

When the quantity of absorbed NO_x in filter 19 approaches the absorption capacity of the NO_x trap wash coat 54 of filter 19, the NO_x regeneration

25   routine for this filter is initiated. At such time, control valve 25 is actuated to a fully opened position, and control valve 24 is set to a partially opened position to restrict the flow of exhaust gases through intake conduit 16. Diesel fuel from the

30   supply 28 is injected by nozzle or valve 29 into intake conduit 16 and is carried toward filter 19 by the restricted exhaust flow in conduit 16. Fuel is injected such that the fuel quantity exceeds the

stoichiometric amount required to completely react and consume all of the oxygen contained within the exhaust gases flowing through conduit 16. In other words, the mixture of exhaust gases and fuel is rich

5   of stoichiometry. Catalytic combustion of the injected fuel occurs in oxidation catalyst 26. Excess fuel is carried downstream into filter 19 and reacts with the absorbed NO_x, thereby regenerating NO_x trap wash coat 54 within filter 19.

10   During the NO_x trap wash coat regeneration process, a substantial exothermic temperature rise occurs within oxidation catalyst 26 when catalyst 26 is oxidizing a rich mixture of exhaust gases and fuel. By locating the catalyst 26 upstream of NO_x

15   trap-particulate filter 19, relatively large temperature spikes caused by an exothermic energy release occur primarily in catalyst 26. Thus, a temperature of exhaust gases exiting catalyst 26 are maintained at a relatively uniform desired

20   temperature which prevents thermal damage to filter 19. Because filter 19 is proximate catalyst 26, the temperature of filter 19 corresponds to the temperature of exhaust gases exiting catalyst 26. Further, locating catalyst 26 adjacent and upstream

25   of filter 19 allow for high molecular weight hydrocarbons within the diesel fuel to be cracked and partially oxidized by catalyst 26 (producing shorter chained hydrocarbons and CO/H_2) before entering filter 19. The shorter chained hydrocarbons vaporize at

30   lower temperatures than non-oxidized hydrocarbons allowing for more effective NO_x regeneration of filter 19.

When regeneration of NO_x trap wash coat of filter 19 is complete, the diesel fuel injection is discontinued, and the control valve 24 is closed. At such time, all of the exhaust gases created by

5   engine 12 will be flowing through exhaust intake conduit 18, oxidation catalyst 27, filter 20, output conduit 22, and tail pipe 23. When the NO_x trap wash coat 54 of filter 20 becomes saturated, the above process is repeated for filter 20.

10   At the same time the level of absorbed NO_x is being monitored in filters 19, 20, the amount of accumulated particulate matter and accumulated SO_x (within NO_x trap wash coat 54) is monitored as well. The removal of particulate matter and desulfation

15   processes can be accomplished in a single step. For example, when the accumulation of particulate matter and the buildup of SO_x within the NO_x trap wash coat of filter 19 exceeds a predetermined level, control valve 25 is fully opened and the control valve 24 is

20   set to a partially opened position. Diesel fuel from the supply 28 is introduced through the nozzle or valve 29 into intake conduit 16 and carried towards filter 19 by the restricted exhaust flow. The rate of diesel fuel injection is set to obtain a rich air-

25   fuel ratio needed to remove the absorbed SO_x. The time interval for the fuel injection and the time interval between subsequent injections are determined to provide the exothermic temperature rise required to desorb SOx from the NOx trap and to initiate

30   oxidation of the particulate matter or soot in filter 19. The temperature sensor 31 provides a feedback control signal to ECM 34 to provide the fuel metering and timing control. Once the temperature of the

filter 19 is maintained above a threshold temperature for removing SO_x and particulate matter, fuel is delivered at periodic intervals to the exhaust gases. Thus, the exhaust gases are alternated between rich

5   of stoichiometry and lean of stoichiometry. During delivery of rich exhaust gases, the SO_x is removed from filter 19. During delivery of lean exhaust gases, particulate matter is removed from filter 19.

Referring to Figures 3A, 3B, 4A-4C, the

10   method executed by ECM 34 to control the exhaust gas purification system 10 will now be described. Figures 3A and 3B describe a preferred control arrangement for monitoring NO_x absorption in filters 19, 20 and regeneration of the same. As shown in

15   Figure 3A, the primary NO_x control scheme begins with a series of initializations. In these logic control diagrams, the parallel filter arrangement as shown in Figure 1 is considered to have two sides or paths. Thus, logic variables ending in the numeral "1" refer

20   to the exhaust path containing filter 19 and logic variables ending in the numeral "2" refer to the exhaust path containing filter 20.

At step 60, the regeneration flags REGNFLG1 and RGENFLG2 for filters 19, 20, respectively are

25   initialized to zero---indicating that particulate matter (PM) removal and desulfation (SO_x regeneration) is not taking place.

At step 62, the values CUMNO1 and CUMNO2 corresponding to the cumulative NO_x stored in filters

30   19, 20, respectively, are initialized to zero.

At step 64, the NOx regeneration counter DNOXCNT and the maximum value of the NOx regeneration counter are initialized to zero.

At step 66, the status of control valves 24, 25 are initialized. In this example, the control valve 24 is fully opened (VFLG1=1) and valve 25 is completely closed (VFLG2=0). The flags VFLG1 and

5 VFLG2 indicate a partially open position when equal to the value of two. After initializing the foregoing variables, all of the exhaust gases will be flowing through filter 19.

At block 68, the mass of feed gas NO_x (MNOX)

10 generated by engine 12 is estimated as a function of the engine speed and load 70. The value MNOX can be readily determined from lookup tables indexed by engine speed and load created during engine mapping.

Because VFLG1 is initially equal to "1",

15 the method advances from step 72 to step 74. At step 74, the value MNOX is added to the cumulative NO_x (CUMNO1) absorbed by filter 19 through which the exhaust gases are flowing.

At step 76, the value RGENFLG2 indicating

20 whether particulate matter and SO_x regeneration is occurring for filter 20 is checked. If regeneration and particulate matter burn-off is not occurring in filter 20, then the method advances to step 78. Otherwise, the method returns to step 68.

25 At step 78, a determination is made as to whether the total mass of absorbed NO_x (CUMNO1) is greater than or equal to a predetermined maximum value (CUMNO_MAX) for filter 19. If the value of step 78 equals "No", the NO_x regeneration program

30 (DNOX2) for the filter 20 is executed. Otherwise, the steps 80, 82, 84, 86 are performed.

At step 80, control valve 24 is partially closed. At step 82, the duration of the NO_x

regeneration (DNOXCNT_MAX) for filter 19 is set as a function of the total NO_x absorbed. Next at step 84, the regeneration timer DNOXCNT is reset. Finally, at step 86, control valve 25 is fully opened.

5   Referring to Figure 3B, the DNOX2 routine for removing NOx from filter 20 will now be described. Before entering the DNOX2 routine, control valve 24 will be fully open and control valve 25 will be partially open.

10   At step 94, a determination is made as to whether the regeneration counter DNOXCNT is greater than or equal to the count DNOXCNT_MAX. The value of the maximum count DNOXCNT_MAX corresponds to the amount of time required to remove the stored NO_x in

15   filter 20 (Fig. 3A, step 92). If the value of step 94 equals "Yes", the method if exited at step 110. Otherwise, the method advances to step 95. At step 95, a partially open position of valve 25 is determined. As shown, the position of valve 25 is

20   determined from exhaust flow rate 97 and exhaust oxygen concentration 100. The exhaust flow rate 97 is determined as a function of engine speed 96. The exhaust oxygen concentration 100 is determined as a function of engine load 99. After step 95, the

25   method advances to step 98.

At step 98, the amount of fuel flow F2 that is injected by injector 30 is determined. The fuel flow amount is calculated based on the exhaust flow rate 97 and the exhaust oxygen concentration 100.

30   At step 101, a determination is made as to whether the temperature T1 of oxidation catalyst 32 is greater than a threshold temperature T_THRESHOLD for optimal removal of NOx. The temperature

T_THRESHOLD may be 270° C for example. If the value
of step 101 equals "Yes", the method advances to step
102 which determines whether the temperature is
greater than a maximum temperature T_MAX. The value
5   of T_MAX may be 400 °C for example. If the value of
step 102 equals "Yes", the opened position V2 of
valve 25 is reduced using the following equation:

$$V2 = V2 - \Delta V$$

where ΔV is a predetermined adjustment amount of
10 valve 25 that is empirically determined. After step
103, the method returns to step 98 to recalculate the
fuel flow F2 based on the new position of valve 25.

Referring again to step 101, if the
temperature T1 is less than threshold temperature
15 T_THRESHOLD for optimal removal of NOx, the method
advances to step 104.

At step 104, the fuel flow F2 is increased
based on the following equation:

$$F2 = F2 + \Delta F$$

20 where ΔF is a predetermined fueling adjustment amount
for valve 30 that is empirically determined. The
step 104 increases the amount of fuel combusted in
oxidation catalyst 27 to thereby increase the
temperature of catalyst 27 and filter 20.

25 Next at step 105, the counter DNOXCNT is
incremented using the following equation:

$$DNOXCNT = DNOXCNT + DT$$

where DT corresponds to the time interval that has
elapsed since the value DNOXCNT was previously
30 incremented in this execution of the DNOX2 routine.

Next at step 106, a determination is made
as to whether DNOXCNT is greater than or equal to
maximum count DNOXCNT_MAX. If the value of step 106

13

equals "No", the method is exited at step 110. Otherwise, the method advances to step 107.

At step 107, the fuel flow F2 is set equal to zero thereby stopping the fuel flow from valve 30.

5   Next at step 108, the throttle valve 25 is closed and the flag VFLG2 is set equal to zero.

Next at step 109, the cumulative stored NOx value CUMNO2 is set equal to zero. Thereafter, the method is exited at step 110.

10   Although not shown, the DNOX1 regeneration routine for filter 19 is performed in a similar manner as described in routine DNOX2, except that valves 24, 29 are controlled instead of valves 25, 30, respectively. The DNOX1 regeneration routine for

15   filter 19 is called from step 91 of Figure 3A.

Referring to Figures 4A, 4B, 4C, the routines for removing particulate matter and SO_x from filter 19 will now be described. The variables ending in the numeral "1" refer to the exhaust path

20   communicating with filter 19 and variables ending in the numeral "2" refer to the exhaust path communicating with filter 20.

Referring to Figure 4A, the Main Particulate Matter and SOXREG Routine is illustrated.

25   At step 200, the regeneration flags are REGNFLG1 and REGNFLG2 are initialized to zero.

At step 202, the accumulated particulate matter counts CUMPM1 and CUMPM2 for filters 19, 20, respectively are initialized to zero.

30   At step 204, the accumulated sulfur counts CUMSOX1 and CUMSOX2 for filters 19, 20, respectively, are initialized to zero. At step 206, the first

14

valve 24 is opened (VFLG1=1) and the second valve 25
is closed (VFLG2=0).

At step 208, the mass of particulate matter
flowing through the first path is determined as a
function of the engine speed/load 210.

Next at step 212, the mass of sulfur
flowing through filter 19 is estimated as a function
of the engine fuel flow 214. Since all of the
exhaust is flowing through the first path 16, these
estimated values will be attributed to filter 19 at
steps 218 and 220. If either the accumulated total
particulate matter in filter 19 as governed by
decision step 222, or the total sulfur absorbed by
filter 19 as dictated by decision step 224 exceeds a
predetermined maximum, the PMREG1 routine is executed
to regenerate filter 19.

Before proceeding with a detailed
discussion of the PMREG1 routine for removing
particulate matter from filter 19, a general overview
of the methodology will be explained. Referring to
Figure 5A, the lambda value (λ) corresponding to an
exhaust gas-fuel ratio or an air-fuel ratio of
exhaust gases flowing into oxidation catalyst 26 over
time is illustrated. As shown, prior to time T_1,
lambda (λ) is lean of stoichiometry. Between times
T_1-T_2, lambda (λ) is reduced to a more rich value.
Lambda (λ) may be made more rich by (i) throttling
valve 24 to reduce the amount of exhaust gases
flowing into catalyst 26 and (ii) injecting
reductant, such as diesel fuel, via valve 29 into the
exhaust gases flowing into catalyst 26. Referring to
Figure 5B, during the injection of fuel during time
interval T_1-T_2, the fuel is completely combusted in

15

catalyst 26 increasing the temperature of exhaust gases entering filter 19. At time T_2, the temperature T1 of catalyst 26 increases above a temperature TCRIT. The temperature TCRIT corresponds to a

5　temperature above which particulate matter and SO_x can be removed from filter 19. For example, TCRIT may be greater than or equal to 600°C. As illustrated, the lean mixture of exhaust gases burns off the particulate matter in filter 19 over the time period

10　DPMTIME_MAX.

Referring to Figure 4B, the PMREG1 routine for removing particulate matter from filter 19 is illustrated. The PMREG1 routine is called by step 226 of Figure 4A.

15　At step 230, the regeneration flag RGENFLG1 is initialized to a value of one indicating regeneration has commenced.

Next at step 232, the first valve 24 is partially opened (VFLG1=2) and the second valve 25 is

20　opened fully (VFLG2=1).

Next at step 234, the particulate matter burn-off time DPMTIME is initialized and the SO_x regeneration time DSOXTIME is initialized. The value DPMTIME corresponds to an amount of time that

25　particulate matter has been burned off of filter 19. The value DSOXTIME corresponds to an amount of time that SO_x has been removed from filter 19.

Next at step 236, a determination is made as to whether the cumulative amount of stored SO_x

30　value CUMSOX1 is greater than or equal to the value CUMSOX1_MAX. If the value of step 236 equals "Yes", the method advances to step 238 that initializes the values DPMCNT and DSOXCNT. Thereafter, the routine

16

SOXREG1-PMREG1 is executed to purge both SO_x and
particulate matter from filter 19. Alternately, if
the value of step 236 equals "No", only particulate
matter regeneration is required and the method

5   advances to step 240.

Next at step 240, the partially open
position V1 for valve 24 is determined as a function
of the exhaust flow rate 242 and exhaust
concentration 246. The exhaust flow rate 242 is

10   determined from engine speed 244. The exhaust
concentration 246 is determined based on engine load
248.

Next at step 250, the fuel flow rate F1
that is delivered by valve 29 into the exhaust gases

15   upstream of oxidation catalyst 26 is determined based
on exhaust flow rate 242 and exhaust oxygen
concentration 246. The injected fuel results in
catalytic combustion over oxidation catalyst 26 in
the first exhaust path and a corresponding exothermic

20   reaction. The reaction is allowed to continue until
the temperature reaches a threshold temperature TCRIT
where sustained oxidation of particulate matter on in
filter 19 is achieved. The mixture of exhaust gases
and fuel entering oxidation catalyst 26 may be lean

25   of stoichiometry. Alternately, when a faster
temperature increase is desired in oxidation
catalyst, the mixture may initially be rich of
stoichiometry until a temperature above TCRIT is
achieved.

30   At step 252, a determination is made as to
whether temperature T1 downstream of oxidation
catalyst 26 is greater than temperature TCRIT. If
the value of step 252 equals "No", the method re-

executes steps 240 and 250 to increase the
temperature T1. Otherwise, the method advances to
step 254.

At step 254, fuel flow through valve 29 is
5   shut off. In other words, no further reductant is
provided to oxidation catalyst 26 once sustained
oxidation of the soot has been achieved in filter 19.

Next at step 256, the counter DPMTIME is
incremented utilizing the following equation:

10   DPMTIME = DPMTIME + DT
where DT corresponds to the amount of elapsed time
since the value DPMTIME was last incremented during
this execution of the PMREG1 routine.

Next at step 258, a determination is made
15   as to whether the value DPMTIME is greater than or
equal to a maximum allowable time DPMTIME_MAX for
removing the particulate matter. If the value of
step 258 equals "No", the method advances back to
step 240 for continued oxidation of particulate
20   matter in filter 19. Otherwise, the method advances
to step 260 which sets the total particulate matter
value CUMPM1 equal to zero. Further, the flag
RGENFLG1 is set equal to zero. Thereafter at step
262, the routine is exited and the method returns to
25   the MAIN PM and SOXREG program.

Before proceeding with a detailed
discussion of the SOXREG1-PMREG1 routine for removing
particulate matter and SO_x from filter 19, a general
overview of the methodology will be explained.
30   Referring to Figure 6A, the lambda value (λ)
corresponding to an exhaust gas-fuel ratio of exhaust
gases flowing into oxidation catalyst 26 over time is
illustrated. As shown, lambda (λ) is alternated

18

between being lean of stoichiometry and rich of
stoichiometry. Particulate matter is removed from
filter 19 when lambda (λ) is lean of stoichiometry.
SO_x is removed from filter 19 when lambda (λ) is rich

5   of stoichiometry.

During each time period DSOXCNT_PRD, lambda
(λ) is maintained rich of stoichiometry. A portion
of the rich mixture is combusted on oxidation
catalyst 26 to increase the temperature of the

10   catalyst 26. Further, as illustrated in Figure 6B,
the temperature T1 of catalyst 26 is maintained above
the temperature TCRIT. A remaining non-combusted
portion of the rich mixture removes SO_x stored in
filter 19. During each time period DPMCNT_PRD,

15   lambda (λ) is maintained lean of stoichiometry. The
lean mixture (containing excess oxygen by definition)
burns off particulate matter stored in filter 19.

Referring to Figure 4C, the routine
SOXREG1-PMREG1 for removing SO_x and particulate matter

20   from filter 19 is illustrated.

At step 264, the partially open position V1
for valve 24 is determined as a function of the
exhaust flow rate 242 and exhaust oxygen
concentration 246.

25   Next at step 266, the fuel flow rate F1
delivered into the exhaust gases upstream of catalyst
26 is determined based on exhaust flow rate 242 and
exhaust oxygen concentration 246.

Next at step 268, the intermediate period

30   (DSOXCNT_PRD) for removing SO_x, and the intermediate
period (DPMCNT_PRD) for removing particulate matter
is determined. It should be noted that the sum of
the DSOXCNT_PRD values corresponds to the De-SOx

regeneration period DSOX_TIME_MAX. Similarly, the
sum of the DPMCNT_PRD values correspond to the total
particulate matter regeneration period DPMTIME_MAX.
The values DSOXCNT_PRD and DPMCNT_PRD may be obtained
5   from a table stored in memory 38 indexed by exhaust
flow rate 242, exhaust oxygen concentration 246, and
fueling rate F1.

       As shown in Figure 6A, the periods
DSOXCNT_PRD and DPMCNT_PRD are utilized to create
10   fuel injection pulses to obtain the fuel flow rate F1
(and a desired lambda value). The fuel injection
pulses create a mixture of exhaust gases and fuel
that alternate between being rich of stoichiometry
and lean of stoichiometry. When the mixture is rich
15   of stoichiometry, a portion of the fuel is burned in
oxidation catalyst 26 increasing the temperature of
filter 19. The remaining un-combusted fuel
decomposes stored SOx within the NO_x trap wash coat of
filter 19.
20   Next at step 270, a determination is made
as to whether temperature T1 of oxidation catalyst 26
is greater than temperature TCRIT. If the value of
step 270 equals "No", the method re-executes steps
264 and 266 to increase the temperature T1.
25   Otherwise, the method advances to step 272.

       At step 272, the time DSOXCNT is
incremented utilizing the following equation:
       DSOXCNT = DSOXCNT + DT
where DT corresponds to the elapsed time since the
30   value DSOXCNT was last incremented in this execution
of the SOXREG1-PMREG1 routine.

       Next at step 274, a determination is made
as to whether the value DSOXCNT is greater than or

equal to the value DSOXCNT_PRD. If the value of step
274 equals "No", the method returns to step 264 for
continued delivery of reductant to filter 19 to
remove SO_x from filter 19. Otherwise, the method

5 advances to step 276.

At step 276, the value DSOXTIME is
incremented using the following equation:

DSOXTIME = DSOXTIME + DSOXCNT_PRD

Next at step 278, the fuel flow rate F1 is

10 set equal to zero to create a lean mixture of exhaust
gases for removing particulate matter from filter 19.

Next at step 280, the valve DPMCNT is
incremented using the following equation:

DPMCNT = DPMCNT + DT

15 where DT corresponds to the amount of elapsed time
since the value DPMCNT was last incremented in this
execution of the SOXREG1-PMREG1 routine.

At step 282, a determination is made as to
whether DPMCNT is greater than or equal to

20 regeneration period DPMCNT_PRD. If the value of step
282 equals "Yes", the method returns to step 280 for
continued removal of particulate matter from filter
19. Otherwise, the method advances to step 284.

At step 284, the total measured

25 regeneration time DPMTIME is incremented using the
following equation:

DPMTIME = DPMTIME + DPMCNT_PRD

Next at step 286, a determination is made
as to whether the measured SO_x regeneration time

30 DSOXTIME is greater than or equal to the value
DSOXTIME_MAX. If the value of step 286 equals "Yes",
the method advances to step 288 explained below.

21

Otherwise, the method returns to step 264 described above.

At step 288, a determination is made as to whether the measured particulate matter removal time

5 DPMTIME is greater than or equal to value DPMTIME_MAX. If the value of step 288 equals "No", the method returns to steps 278 for continued removal of particulate matter from filter 19. Otherwise, the method advances to step 290.

10 At step 290, the values CUMSOX1, CUMPM, REGNFLG1 are all set to zero. Thereafter, the routine is exited at step 292.

The system and method for controlling a temperature of an emission control device provides a

15 substantial advantage over known systems and methods. In particular, by controlling a temperature of an oxidation catalyst 26 adjacent the NOx trap 19, the temperature of the NOx trap 19 can also be accurately controlled. As discussed above, this is accomplished

20 by controlling a mixture of exhaust gases and reductant flowing into catalyst 26 to obtain a desired temperature range for gases flowing into the NOx trap 19. Thus, the NOx trap 19 can be maintained within the desired temperature range, preventing

25 degradation of trap 19.